



## FLASH5AV2

2-way processed active loudspeaker system



### Description

FLASH5 is the latest addition to this successful PROEL series of loudspeaker systems. Sharing the same stylish design, hi-tech engineering and superior sound quality of the FLASH family, FLASH5 is the most compact model of the series, designed for a variety of sound reinforcement applications where a full bandwidth, ultra-compact speaker is required.

- Bi-amplified 2-way system
- Studio-grade dome tweeter on elliptical waveguide
- 5 woofer with PP cone
- 200W total peak power
- 20W class AB amplifier for the high frequencies
- 80W class D amplifier for the low frequencies
- XLR, 1/4 JACK and dual RCA connectors
- 2 active EQ presets available (MIDFIELD / NEARFIELD)
- Dual CLIP LIMITER
- SPL MAX 114 dB
- Frequency response 70 Hz - 20 kHz
- Lightweight polypropylene cabinet with extensive framing system
- Symmetrical trapezoidal shape for the use also as a stage monitor
- 1 top handle
- 3 x M6 flying points

### Technical Specifications FLASH5AV2

- System type 2-way vented enclosure
- High Frequency Device Soft dome tweeter on elliptical waveguide
- Low Frequency Device 5 woofer with PP cone
- Angular Coverage 90° H x 60° V
- Total peak power 200 W
- HF Amplifier Continuous Power 20 W Class AB



LF Amplifier Continuous Power 80 W Class D  
Power Supply Linear  
Processing Analog  
Frequency Response 70 Hz - 20 kHz  
Max SPL 114  
Connectors IN/LINK: XLR F, 1/4" JACK, 2 x RCA  
Controls LEVEL, NEARFIELD/MIDFIELD, GND LIFT  
Power Supply 230 VAC or 120 VAC 50/60 Hz  
Weight 3.6 kg (7.9 lb)  
Monitor Taper 42°  
Flying System 3 x M6 - top/bottom  
Construction Polypropylene  
Cabinet Colour Black/White  
Dimensions (W x H x D) 175 x 265 x 176.5 mm

